POMI

Miniwrap 60



- Pressing and wrapping in one cycle.
 - Easy handling of bales 30 to 60 kg.
 - Recommendable for small-scale animal husbandry.
 - No storage place required store outdoors.





The Miniwrap 60 bale wrapper is the ideal solution where efficient handling of easy-to-handle 30 to 60 kilo round bales is requried.

Miniwrap 60 is atractive for small-scale husbandry where the saily feed consumption is under 30 to 60 kilos and where out door storage may be disirable.



Computer-controlled wrapping from tractor enables continuously variable setting of wrap layers.

Continuously variable adjustment of film pre-stretch from 40 to 60 %.

Fully automated cutting of film and loading/unloading of round bales fully sunchronized with Miniwrap 60.

Hydraulic drive of winder arm and rollers ensuring precise wrapping.







MINIWRAP 60

Overall length with bale press: 3675 mm.
Overall width with bale press: 1800 mm.
Overall height with bale press: 1500 mm.
Overall weight with bale press MB 60: 840 kg.
Weight, film roll: 12 kg.

Capacity: 30 to 50 bales/hr.

Consumption of film: 36 bales/roll at 6 layers. *)

Rotation speed: 50 rpm

Requirements of tractor:

Power required: Min. 40 HP.

Hydraulic oil connection: 1 double-acting/min. 23 litres/min.

Voltage: 12 V 8 Amp.

*) 300 mm / 1800 m / 25mu.

CE

All components meet the 98/37/EEC Machine Directive safety requirements.

POMI Industri Aps

Abildvadvej 5, Thorup DK-9610 Nørager

Tel. +45 98 55 20 00 Fax +45 98 55 22 00 www.pomi.dk Mail: pomi@pomi.dk

Distrubutor's stamp:

Distributor