

POMI

Stack 200



See video on
www.pomi.dk



- ✓ Amazingly simple bale pick up.
- ✓ Handles a variety of bale sizes.
- ✓ Saves time and improves your economy.
- ✓ Easy bale stacking.

The **STACK200** bale stacker allows you to collect and stack up to 120 bales per hour. The bale stacker has benne designed by an experienced and innovative large-scale farmer for the purpose of increasing efficiency on his farm.

The **STACK200** collects the bales while moving in the same direction as the baler so you avoid having to cross the baler's tracks in the field. Leaf-sprung axles, flotation tyres and a hydraulically operated support wheel provide a smooth and steady ride across the field. The bale gripper carefully picks up the bales from the field and centres them on the loading platform. Here the bales are stacked in pairs before they are tipped onto the trailer.

The bales are kept in place on the **STACK 200** by the hydraulic side guard and two supporting forks which automatically adjust their position while loading the trailer. The trailer primarily consists of rollers which easily move wrapped bales even when they are drenched.

The supporting forks and the side guard on the **STACK 200** keep the loaded bales in place when you tip the trailer to unload the entire stack. The **STACK 200** features a tip stabilizer which locks the rear axle of the trailer when unloading the bales. The bales are unloaded in the same position as they were picked up from the field, i.e. with the knots turned upwards.

The hydraulic drawbar makes it easy to switch between **STACK200** operation mode and transport mode.



The bale gripper is easily adjusted to different bale sizes. It ensures that the bales are centred on the loading platform.



A special push-off mechanism makes it easy to pull out the forks from underneath the stack no matter if the surface is of soil, cement or asphalt.

Technical specifications	
Length, total	9.100 mm
Widh, total	2.500 mm
Height, total	3.900 mm
Weight, total	6.000 kg
Front lift capacity	1.000 kg
Loading	8.000 kg
Recommended specifications for tractor	Min. 100 HK - 50 L/min.

Bale size capacity	
120 x 130 cm	8 bales
120 x 90 cm	12 bales
120 x 80 cm	12 bales
120 x 70 cm	14 bales
80 x 90 cm	18 bales
80 x 80 cm	18 bales
80 x 70 cm	21 bales

POMI Industri ApS

Abildvadvej 5, Thorup • DK-9610 Nørager
Tlf. +45 9855 2000 • Fax +45 9855 2200

www.pomi.dk

Dealer: